Applicants: Sydir et al. Attorney's Docket No.: INTEL-014PUS Intel Docket No. P17941

Serial No.: 10/749,035

Filed: December 30, 2003

Page : 2 of 7

**AMENDMENTS TO THE CLAIMS:** 

This listing of claims replaces all prior versions and listings of claims in the

application:

**LISTING OF CLAIMS:** 

1. (Previously Presented) A processor, comprising:

a crypto system;

an alignment buffer to receive header data and ciphered data from the crypto system, the

crypto system encrypting data to form ciphered data so that an intended receiver with a correct

cryptographic key may decrypt the ciphered data; and

a switch fabric having a plurality of transmit buffer elements to receive data from the

alignment buffer, wherein the alignment buffer provides data to the switch fabric in blocks

having a predetermined size,

wherein the crypto system comprises a plurality of crypto unit processing contexts and

the alignment buffer comprises a number of buffer elements equal to a number of processing

contexts, and

wherein the plurality of processing contexts are configured to process at least one data

packet at a time and to store cipher keys and algorithm context associated with processing the at

least one data packet.

Applicants: Sydir et al.
Serial No.: 10/749,035
Filed: December 30, 2003
Page: 3 of 7 Attorney's Docket No.: INTEL-014PUS Intel Docket No. P17941

2. (Previously Presented) The processor according to claim 1, further including an interface to transmit data from the switch fabric.

3. (Previously Presented) The processor according to claim 2, wherein the interface includes a SPI4 type interface.

4. (Previously Presented) The processor according to claim 2, wherein the interface includes an NPSI interface.

5. (Previously Presented) The processor according to claim 1, wherein the crypto system includes first and second crypto units.

Claim 6 (Cancelled)

- 7. (Previously Presented) The processor according to claim 1, wherein the crypto system includes a plurality of cipher cores.
- 8. (Previously Presented) The processor according to claim 7, wherein the plurality of cipher cores correspond to a plurality of cipher algorithms.

Claims 9 to 20 (Cancelled)

Applicants: Sydir et al.

Serial No.: 10/749,035

Filed

: December 30, 2003

Page

Attorney's Docket No.: INTEL-014PUS

Intel Docket No. P17941

21. (Previously Presented) A network switching device, comprising:

a processor disposed on an integrated circuit comprising:

a crypto system, the crypto system encrypting data to form ciphered data so that

an intended receiver with a correct cryptographic key may decrypt the ciphered data, the

crypto system comprises a plurality of crypto unit processing contexts and the alignment

buffer comprises a number of buffer elements equal to a number of processing contexts;

an alignment buffer to receive header data and the ciphered data from the crypto

system; and

a switch fabric interface unit having a plurality of transmit buffer elements to

receive the ciphered data from the alignment buffer, wherein the alignment buffer

provides the ciphered data to the switch fabric in blocks having a predetermined size,

wherein the plurality of processing contexts are configured to process at least one data

packet at a time and to store cipher keys and algorithm context associated with processing the at

least one data packet.

22. (Cancelled)

23. (Original) The device according to claim 21, wherein the crypto system includes a

plurality of cipher cores,

wherein the plurality of cipher cores correspond to a plurality of cipher algorithms.

Applicants: Sydir et al. Attorney's Docket No.: INTEL-014PUS
Serial No.: 10/749,035

Attorney's Docket No.: INTEL-014PUS
Intel Docket No. P17941

Serial No.: 10/749,035 Filed: December 30, 2003

Page : 5 of 7

24. (Original) The device according to claim 21, wherein the device includes a router.

25. (Previously Presented) A network, comprising:

a network switching device including a processor disposed on an integrated circuit

comprising:

a crypto system, the crypto system encrypting data to form ciphered data so that

an intended receiver with a correct cryptographic key may decrypt the ciphered data;

an alignment buffer to receive header data and the ciphered data from the crypto

system; and

a switch fabric interface unit having a plurality of transmit buffer elements to

receive the ciphered data from the alignment buffer, wherein the alignment buffer

provides the ciphered data to the switch fabric in blocks having a predetermined size,

wherein the crypto system comprises a plurality of crypto unit processing contexts and

the alignment buffer comprises a number of buffer elements equal to a number of processing

contexts, and

wherein the plurality of processing contexts are configured to process at least one data

packet at a time and to store cipher keys and algorithm context associated with processing the at

least one data packet.

Claim 26 (Cancelled)

Applicants: Sydir et al. Serial No.: 10/749,035

Filed : December 30, 2003

Page : 6 of 7

27. (Previously Presented) The network according to claim 25, wherein the crypto system includes a plurality of cipher cores.

Attorney's Docket No.: INTEL-014PUS

Intel Docket No. P17941

28. (Original) The network according to claim 25, wherein the network switching device corresponds to a router.

Claim 29 (Cancelled)